# PATENT ABSTRACTS OF JAPAN

(11)Publication number:

08-329464

(43) Date of publication of application: 13.12.1996

(51)Int.CI.

G11B 5/85 G11B 5/66

G11B 5/84 H01F 41/22

(21)Application number: 07-136688

(71)Applicant: KAO CORP

(22)Date of filing:

02.06.1995

(72)Inventor: KOBAYASHI ISAO

## (54) PRODUCTION OF MAGNETIC RECORDING MEDIUM

(57)Abstract:

PURPOSE: To obtain a magnetic recording medium having high coercive force and adaptable to high recording density with a low-cost Co-Sm alloy material as the material of a magnetic recording layer.

CONSTITUTION: A film of Cr as an underlayer, a film of a Co100-x-y-Smx-Ry alloy [R is a rare earth element other than Sm, (x) is 1-30at.% and (y) is 0-10at.%] as a magnetic recording layer and a film of Cr as an upper layer are formed on an amorphous carbon substrate at ≤ 400°C temp. of the substrate and then heating is carried out. at 250-650°C in inert gas or in vacuum.



#### **LEGAL STATUS**

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]



[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's


decision of rejection]

[Date of requesting appeal against examiner's

decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2000 Japan Patent Office



### PATENT ABSTRACTS OF JAPAN

(11)Publication number:

08-329464

(43)Date of publication of application: 13.12.1996

(51)Int.CI.

G11B 5/66 G11B 5/84 G11B H01F 41/22

(21)Application number: 07-136688

(71)Applicant:

**KAO CORP** 

(22)Date of filing:

02.06.1995

(72)Inventor:

**KOBAYASHI ISAO** 

(54) PRODUCTION OF MAGNETIC RECORDING MEDIUM

(57)Abstract:

PURPOSE: To obtain a magnetic recording medium having high coercive force and adaptable to high recording density with a low-cost Co-Sm alloy material as the material of a magnetic recording layer.

CONSTITUTION: A film of Cr as an underlayer, a film of a Co100-x-y-Smx-Ry alloy [R is a rare earth element other than Sm, (x) is 1-30at% and (y) is 0-10at%] as a magnetic recording layer and a film of Cr as an upper layer are formed on an amorphous carbon substrate at ≤400° C temp. of the substrate and then heating is carried out. at 250-650° C in inert gas or in vacuum.

■: SIO2 M . Cr 磁気配母和:Со-9 m

#### **LEGAL STATUS**

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Daté of requesting appeal against examiner's decision of rejection]

[Dat of extinction of right]

Copyright (C); 1998,2000 Japan Patent Office